



THE SCIENCE OF SURVIVAL

# ACR EPIRB Accessories

For 406 MHz Beacons



## EPIRB



Scan With Phone  
[www.ACRARTEX.com](http://www.ACRARTEX.com)



# ACR EPIRB Accessories

For 406 MHz Beacons



## Sea Shelter™<sub>3</sub> Category I Bracket

This fully enclosed, robust bracket provides EPIRB protection in the harshest conditions, and automatically deploys your EPIRB should your vessel sink. The quick-release latch allows for fast, easy top cover removal, even with gloves on. Ideal for use in fishing, petrochemical, freighter, salvage or any other harsh marine applications. The Sea Shelter™<sub>3</sub> also features a streamlined, aesthetic design perfect for yachts or racing vessels.

- Innovative, quick-change hydrostatic release mechanism
- One-way mounting eliminates the possibility of installing EPIRB backwards
- Integral de-activation magnet prevents the EPIRB from transmitting until deployed
- Deploys EPIRB when submerged in water at a depth between 4.9 – 13.1 ft (1.5 – 4 m)
- Hydrostate Release sold separately

## HydroFix™ Hydrostatic Release Unit for Category I EPIRB

A patented rod system does not rely on a battery, blade or pyrotechnic device to release the beacon. This advantage allows for a quick, seamless and reliable release in an emergency. Note that this is a date-stamped product and must be replaced every 2 years from the date of installation or 4 years from the date of manufacture.

- Allows release of a beacon from a Category I bracket when submerged in water between 4.9 – 13.1 ft (1.5 – 4 m)
- Easily replaceable
- 100% factory tested

## LowPro™<sub>3</sub> Category II Bracket

This low-profile bracket features an incredibly small footprint for bulkhead mounting. Made of high-density, UV-stabilized polyethylene, the LowPro™<sub>3</sub> will securely store your GlobalFix™ iPRO/PRO even after years of abuse.

- One-way mounting eliminates the possibility of installing EPIRB backwards
- Integral de-activation magnet prevents the EPIRB from transmitting until deployed
- Two part design allows de-activation magnet to unclip from bracket for storage on the EPIRB in a ditch bag to prevent false alarms

## SPECIFICATIONS

Product Number	9501
Fits	GlobalFix™ iPRO (P/N 2846.0), GlobalFix™ PRO (P/N 2842)
Size	14.3 x 5.9 x 4.7" (36.5 x 15.0 x 12.0 cm)
Weight	2.23 lbs (1.01 kg)



P/N 9501

Product Number	9490
Fits	Open Face™, Sea Shelter™, Sea Shelter™ <sub>2</sub> and Sea Shelter™ <sub>3</sub> brackets
Size	2.5 x 3.4 x 2.0" (6.3 x 8.6 x 5.0 cm)
Weight	3.3 oz (93.6 g)



P/N 9490

Product Number	9502
Fits	Satellite 406™, Satellite <sub>2</sub> 406™, RapidFix™ 406, GlobalFix™ (RLB-35)
Size	5.2 x 6.9 x 2.6" ( 13.3 x 17.4 x 6.4 cm)
Weight	5.0 oz (141 g)



P/N 9502



Satellite 406™

GlobalFix™ PRO

GlobalFix™ iPRO

ACR Authorized Dealer:

**United SAR, Inc.**

5904 E Adamo Dr

Tampa, FL 33619

Tel: (813) 621.5052

Fax: (813) 441.7813

Email: sales@unitedsar.com

THE SCIENCE OF SURVIVAL