

## ACR THE SCIENCE OF SURVIVAL

# BUOYANT MARKER LIGHT

The SM-3 is a high intensity LED strobe which provides 360° visibility for approximately 2 miles. This compact yet durable marker light facilitates rescue by automatically activating and beginning to strobe when in the water, working for over 40 hours at 30°C (86°F) or over 24 hours at -1°C (30°F). Perfect for commercial marine, petro-marine, cruisers, and any other application needing a reliable Crew Overboard Marker (COB) light, the SM-3 floats upright in all conditions, ensuring it will keep shining when you need it the most.



User Replaceable AA Lithium Batteries



**Built-in Buoyancy** 



LED Strobe Light



www.ACRARTEX.com

## SM-3 BUOYANT MARKER LIGHT

With a minimum light intensity of 3 candelas throughout its entire operating life, this high intensity LED strobe clearly marks a crew-overboard site with each brilliant flash. It automatically rights itself and activates when in the water, ensuring that activation is never an issue that a crew member in distress needs to worry about. The SM-3 operates on 2 AA Lithium batteries and the batteries are user replaceable, allowing the potential for a longer product life than the many disposable lifebuoy lights on the market.

The supplied mounting bracket holds the SM-3 secure in the roughest of conditions but it is still readily accessible when needed in an emergency. Additionally, while the SM-3 and its bracket are significantly smaller than the SM-2 counterparts, the SM-3 bracket conveniently maintains the same mounting hole pattern as the SM-2, allowing for easy retrofit with no additional adapter plate required.

The SM-3 is USCG/MED/SOLAS approved for use around the world and this durable LED marker light therefore provides an excellent option for vessels needing to meet USCG and SOLAS carriage requirements for lifebuoy selfigniting lights. As per USCG and SOLAS requirements for passenger and cargo vessels, at least one-half of the total number of lifebuoys on the vessel must be fitted with a selfigniting light. Minimum carriage requirements are based on the length of the vessel and can range from a minimum of four to a minimum of fifteen lifebuoys with self-igniting lights per vessel.

With its easily replaceable Lithium AA battery power source, the SM-3 will give years of service and be ready when called upon.



LED Strobe Light



**User Replaceable AA Lithium Batteries** 



Small and Lightweight Design

### SPECIFICATIONS

Product Number: 3947 Model Number: SM-3

#### Operation

Throw SM-3 overboard or turn upright and strobe light will automatically begin to flash

Batterv

2 AA Lithium Batteries (L91) / User Replaceable (Not Included)

Material UV Resistant Polycarbonate

Color International Safety Orange

Activation

Automatic gravity switch Flash Rate

50-70 times per minute

#### Weight

0.66 lbs (300 g) Light Only 0.71 lbs (330 g) Light with Batteries 0.90 lbs (406 g) Light with Batteries & Bracket

#### Warranty

1 Year

Bouvant Yes

Approvals

USCG, MED, & SOLAS (see www.acrartex.com for full list of approvals) Drop Test

Drop tested to 76 meters (USCG/SOLAS/MED only call for 30 meters)

#### **Operational Life**

40 hours over 3 cd at 30°C (86°F) / 24 hours over 3 cd at -1°C (30°F) Size

9.9" (253 mm) Length / 2.2" (56 mm) Diameter

#### **Light Intensity**

LED with a minimum of 3 candelas per flash in all directions

#### Visibility

360° visibility

#### Mounting Bracket

UV resistant polycarbonate bracket included / Same mounting hole pattern as previous SM-2 Model for easy retrofit

Authorized ACR Dealer:

United SAR, Inc. 5904 E Adamo Dr Tampa, FL 33619 Tel: (813) 621.5052 Email: sales@unitedsar.com

#### For further information please contact: **ACR Electronics, Inc.**

5757 Ravenswood Road Fort Lauderdale, FL 33312

www.ACRARTEX.com

This document is the property of ACR Electronics, Inc. (ACR) and is distributed by ACR for the benefit of our customers. This document may not be disseminated, reproduced or altered in any way without the prior written approval of ACR Electronics, Inc.

**Rugged Build** 



#### **Built-in Buoyancy**

360° Visibility

USCG, SOLAS, & **MED** Approved

& Upgrade from

SM-2

**Easy Installation** 



